



PRODUCT GUIDE- CASSIOPEIA BASE AND FLAKES

Surface Preparation:

Apply PVA primer.

Application:

- Apply one coat of Cassiopeia Base with a delicate roller and wait until fully cured.
- Apply a second coat of Cassiopeia Base with a thicker roller. The thickness of that should be 1 kg/m². When the substance is still wet, spray the glitter and glass flakes on the wall until a complete and uniform appearance is obtained (300-400 gr. of flakes / m²).
- After the wall is dry, go over it with a brush and remove
- PLC Lacquer can be applied to the entire surface.

Note:

Cassiopeia Base colors are shaded in accordance with any color fan, with roller or compressor spraying. The glitter and glass flakes are to be applied with spray gun with an aperture (nozzle) at least 4mm wide (in order to enable the glass flakes to exit). The most attractive appearance is obtained when background is dark and the glass flakes sparkle on it in a wide range of colors. Cassiopeia base color are tintable in accordance with any paint manufacturer color fan deck.

Expert Recommendation:

Practice the spraying technique on a small area before starting the project. Cover the floor with clean polyethylene sheeting and collect the glitter and glass flakes that drop, for reuse.

Lighting:

Lighting plays a decisive role in the final appearance. We recommend spotlights illumination at a distance of three meters, in order to obtain a splendid look.

Coverage:

5 kg 90-100 sq. ft. for two coats; depending on surface and texture.