

Revision Date: 09/09/2020

Tonachino Firenze

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/PREPERATION AND OF THE COMPANY/UNDERTAKING

1.1 Product details

Product category : Tonachino Firenze
Product Name : Product Name
Cas-No. : Mixture

1.2 Application/preparation of the substance : Fine seasoned slaked lime based coating

Restrictions : None known

1.3 Details of the Manufacturer/Supplier : Meoded Paints & Decoration Inc.

: 6314 Santa Monica Blvd: Los Angeles, CA 90038

Further Information Obtainable from : lnfo@meodedpaint.com

Contact Phone Number : *1 323-308-2600 Fax : *1 323-308-2606 In case of emergency, contact CHEMTREC : *1 800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture in accordance with (OSHA HCS) 29 CFR 1910, 1200.

Classification : Not classified.

2.2 Pictogram (GHS-US)

1.4







Signal Word (GHS-US) : Danger

Hazard statement(s) (GHS-US) : H361 Suspected of damaging fertility or the unborn

child.

: H350 May cause cancer.

: H318 Causes serious eye damage.

: H315 Causes skin irritation.

: H335 May cause respiratory irritation.

Precautionary statement(s) (GHS-US) : P101 If medical advice is needed, have product

container or label on hand.

: P102 Keep out of reach of children.

: P201 Obtain special instructions before use.

Do no breathe dust.

: P284 (In case of Inadequate ventilation) wear a

respiratory protection.

(Contd. on page 2)

Meoded Paint & Plaster Page 1 of 10



Revision Date: 09/09/2020

Tonachino Firenze

(Contd. of page 1)

Precautionary statement(s) (GHS-US) : P280 Wear protective gloves/protective clothing/eye

protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

: P305+P351 IF IN EYES: Rinse cautiously with water for

several minutes.

Response statement(s) (GHS-US) : P304+P340 IF INHALED: Remove victim to fresh air and keep

at rest in a position comfortable for breathing.

: P301+P310 IF SWALLOWED: Immediately call a POISON

CENTER or doctor/physician.

Storage Statement(S) (GHS-US) : P402 Store in a dry place.

Disposal Statement(s) (GHS-US) : P501 Dispose of contents/container to in accordance

with local/regional/national/international

regulations.

SECTION 3: COMPOSITION/INFORMATION ON IGREDIENTS

3.1 Composition/information on ingredients.

Dangerous components.

Component	Cas #	Exposure Limit	
Titanium Dioxide	13463-67-7	OSHA PEL (Respirable)	15 mg/m ³
		ACGIH TLV (Respirable)	10 mg/m ³
Quartz (Crystalline Silicate)		OSHA PEL (Respirable Quartz)	10 mg/m³ / (% silica + 2)
	148080-60-7	OSHA PEL (Quartz) 30 mg/m³ / (30 mg/m ³ / (% silica ⁺ 2)
		ACGIH TLV (Respirable)	0.025 mg/m ³ / (Respirable)
Calcium Hydroxide	1305-62-0	OSHA PEL (Respirable)	15 mg/m ³
		ACGIH TLV (Respirable)	5 mg/m ³

3.2 Compositions Comments: : n/a

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice : n/a

Incase of skin contact : Immediately wipe excess material off skin, wash affected

area with plenty of soap and water. Seek medical attention

if irritation develops or persists.

(Contd. on page 3)

Meoded Paint & Plaster Page 2 of 10



Revision Date: 09/09/2020

Tonachino Firenze

(Contd. of page 2)

If swallowed : Do not Induced vomiting. Rinse mouth thoroughly. Get

medical attention immediately.

Incase of eye contact : Rinse immediately with plenty of water, also under the

eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing and seek medical

attention if irritation develops or persists.

If inhaled : Remove to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER

or doctor/physician.

SECTION 5: FIRE FIGHTING MEASURES

5.1 General Fire Hazards : This product is not-flammable.

5.2 Extinguishing Media

Suitable extinguishing media : Water Powder carbon dioxide, foam. Use any means suitable

for extinguishing surrounding fire.

Unsuitable extinguishing media : This product is not-flammable.

5.3 Special hazards arising from the substance : Not known.

or mixture

5.4 Special protective equipment : n/a

5.5 Advice for firefighters : Use protective measures that suit the hazard conditions.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Non emergency personnel : Wear personal protection equipment. Remove person to

safety. Use personal protective equipment as recommended in

section 8. Wash thoroughly after handling mater. Wear

appropriate protective clothing.

For emergency responders : Use personal recommended in Section 8 of the SDS.



Revision Date: 09/09/2020

Tonachino Firenze

(Contd. of page 3)

6.2 **Environmental precautions** : Do not allow to enter into soil/subsoil. Prevent runoff from contacting public drains, sewers, streams, and water systems.

6.3

cleaning

Methods and materials for containing and : Limit leakage with earth or inert material. Remove most of the the product and then rinse the contaminated are with water. Pick up and arrange for disposal without creating dust. Disposed of materials in a suitable containers in accordance with applicable regional, national and local laws and

regulations.

Notification Procedures 6.4

: Caution: Contaminated surfaces may be slippery.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

: Do not handle until all safety precautions have been read and understood. Consult all the other sections of this SDS. Avoid leakage of the product into the environment. Wear protective clothing. Do not breathe dust. Wash thoroughly after handling.

Conditions for safe storage, including any 7.2 inculpabilities

: Store only in original container. Store the container sealed, in a well ventilated place, away from direct sunlight. Keep containers away from incompatible materials. Cross contamination will render product useless.

7.3 Specific end use(s) Decorative Finish.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters 8.1

United States. Occupational limits:			
Component	Cas #	Exposure Limit	
Titanium Dioxide	13463-67-7 -	OSHA PEL (Respirable)	15 mg/m ³
		ACGIH TLV (Respirable)	10 mg/m ³
Quartz (Crystalline Silicate)	148080-60-7	OSHA PEL (Respirable Quartz)	10 mg/m ³ / (% silica + 2)
		OSHA PEL (Quartz)	30 mg/m ³ / (% silica + 2)
		ACGIH TLV (Respirable)	0.025 mg/m ³ / (Respirable)
Calcium Hydroxide	1305-62-0	OSHA PEL (Respirable)	15 mg/m ³
		ACGIH TLV (Respirable)	5 mg/m ³

(Contd. on page 5)

Mended Paint & Plaster Page 4 of 10



Revision Date: 09/09/2020

Tonachino Firenze

8.2 Exposure controls (Contd. of page 4)

Appropriate engineering controls

: Use with adequate ventilation to ensure exposure levels are maintained below the limit provided above. Use exhaust ventilation or other engineering controls to keep airborne levels below specified exposure limits.

Individual Protective Measures General information : Personal protective equipment should be chosen according to applicable standards.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure the eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases, dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection Safety glasses with side shields.

Skin protection Hand protection : Chemical-resistant, impervious gloves complying with approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

(Contd. on page 6)



Revision Date: 09/09/2020

Tonachino Firenze

(Contd. of page 5)

Other skin protection : Appropriate footwear and any additional skin protection

measures should be selected based on the task being

performed and the risks involved and should be approved by

a specialist before handling this product.

Respiratory protection : Based on the hazards and the potential for exposure, select

a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting,

training and other important aspects of use.

Environmental exposure controls : Environmental manager/supervisor must be informed

immediately of all major releases, Avoid unintended release

into the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information in basic physical and chemical properties

Form	Creamy Paste	
Color	Various	
Odor	Slight	
Odor threshold	Not applicable	
PH	12 to 13	
Melting/freezing point	No data available	
Initial boiling point and	No data available	
boiling range	NO data avallable	
Flash point	No data available	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Upper/lower explosive	No data available	
flammable limits	INO uata avallable	
Vapor pressure	No data available	

Vapor density	No data available	
Relative density	No data available	
Water solubility	Miscible	
Partition coefficient	No data available	
(n- octanol water)		
Auto-ignition	No data available	
temperature	NO data avallable	
Decomposition	No data available	
temperature	NO data avallable	
Viscosity	No data available	
Explosive properties	No data available	
Oxidizing properties	No data available	
Specific gravity (H2O=1)		
VOC:	0.0 g/l (0.0 lb./gal)	

9.2 Other Information : No relevant additional information available.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity : Stable under normal conditions.



Revision Date: 09/09/2020

Tonachino Firenze

(Contd. of page 6)

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous

reaction will not occur.

10.4 Conditions to avoid : Air, dusting, and incompatibles. DO NOT FREEZE.

10.5 Incompatible materials : As a strongly alkaline material, it is incompatible with acids.

10.6 Hazardous decomposition products : No date available.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Acute toxicity : Not available

Skin corrosion/irritation : May cause skin irritation. May cause serious chemical burns.

May cause dryness and chopped skin.

Eyes : This product may cause serious ocular lesions, cornea

opacity, iris lesions, irreversible eye coloration.

Respiratory : Vapor inhalation may irritate the lower and upper respiratory

tract and cause cough and respiratory disorders.

Sensitization : No data available.

Mutagenicity : No data available.

Reproductive toxicity : No data available.

Teratogenicity : No data available.

Specific target organ toxicity

(Single exposure)

Ingredient name	Category	Route of exposure	Target Organs
Titanium Dioxide 2B	20	Inhalation and skin contact	Respiratory tract irritation, skin
	initialation and skin contact	irritation	
Quartz (Crystalline Silicate)	1	Inhalation	Respiratory tract and kidneys
Calcium Hydroxide 3	2	Inhalation and skin contact	Respiratory tract irritation, skin
	3		irritation

Meoded Paint & Plaster Page 7 of 10



SAFETY DATA SHEET

Revision Date: 09/09/2020

Tonachino Firenze

(Contd. of page 7)

Additional Information : No data available.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity : Due the high PH of this product, it would be expected

to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems in high concentrations.

12.2 Persistence and degradability : No data available

12.3 Bio accumulative potential : No data available

12.4 Mobility in soil : No data available

12.5 Other adverse effect : No data available

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recycle products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be consider when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal od spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: TRANSPORT INFORMATION

14.1 UN Number : Not regulated

(Contd. on page 9)

Meoded Paint & Plaster Page 8 of 10



SAFETY DATA SHEET

Revision Date: 09/09/2020

Tonachino Firenze

(Contd. of page 8)

14.3 Transport Hazards Class(es) : Not regulated

14.4 Packing Group : Not regulated

14.5 Environmental Hazard Class(es) : This material is high in alkaline if release into water or moist

soil it will cause an increase in PH.

14.6 Sea Transport Not regulated

14.7 Air transport Not regulated

14.8 Special Precautions for user : None

SECTION 15: REGULATORY INFORMATION

15.1 US Federal regulations

OSHA Hazard Communication Standard, (2! : Material is considered Hazardous. See Section 3.

CFR 1910.1200)

15.2 CERLA, section 103 (40 CFR 302.4) : No data available

15.3 CLEAN AIR ACT, section 112 : No data available

15.4 SARA, section 302 (40 CFR 355.30) and

section 304 (40 CFR 355.40)

: No data available

15.5 SARA, section 311/312 (40 CFR 370.21)

Hazard classes

Fire/Flammability : No

Reactivity : No

Chronic Health Hazard : Yes

Acute Health Hazard : Yes

Release of Pressure : No

Meoded Paint & Plaster Page 9 of 10



SAFETY DATA SHEET

Revision Date: 09/09/2020

Tonachino Firenze

(Contd. of page 9)

15.7 EPA VOC : 0.0 g/l VOC

15.8 California Prop 65.

· · · · · · · · · · · · · · · · · · ·		
Titanium Dioxide	Cas#	13463-67-7
Quartz (Crystalline Silicate)	Cas #	148080-60-7

Additional Information:

Cas # 13463-67-7 Titanium Dioxide

: The listing is for titanium dioxide as "airborne, unbound particles of respirable size" and does not cover titanium dioxide when it remains within a product matrix.

SECTION 16: OTHER INFORMATION

16.1 Full text of H-Statements referred to under sections 2 and 3.

HMIS Hazard ID		
HEALTH	1	
FLAMMABILITY	0	
REACTIVITY	0	
PERSONAL PROTECTION	E	

Required Equipment

Safety glasses, Gloves, Respirator

16.1 Meoded Paint and Decoration provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using the product. Individuals receiving the information must exercise their independent judgement in determining its appropriateness for a particular purpose. Meoded Paint and Decoration makes no representation or warranties, either express or implied, including without limitation any warranties of merchantability fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly, Meoded Paint and Decoration will no be responsible for damages resulting from use of or reliance upon this information.

END OF SDS SHEETS

Meoded Paint & Plaster Page 10 of 10