



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA 90038  
1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

## Marmorino Tintoretto™

### Matte/Low Sheen Venetian Plaster

Zero VOC / Eco Friendly

**Meoded Marmorino Tintoretto™** is a natural lime and marble dust paste plaster, which can be used as an interior and exterior matte/low sheen Venetian Plaster. **Marmorino Tintoretto™** is a contemporary version of the traditional smooth Italian stucco which is known for its warmth and dramatic appearance. A wide range of textures can be achieved with **Marmorino Tintoretto™** including marble-like, smooth finish, distressed, or natural stone looks. Due to its natural makeup, **Marmorino Tintoretto™** allows for the creation of a slight matte or a slight sheen finish depending upon type of application. Primarily applied to drywall, concrete, stucco, plaster and gypsum board substrates, the product can also be used to beautify most other smooth-surfaced materials.

### COLORS

**Marmorino Tintoretto™** can be tinted to any color using Universal tints or machine colorants. Meoded's natural concentrated "VOC free" pigments are recommended for dark colors.

### SIZE AND COVERAGE

**Marmorino Tintoretto™** yields a high coverage rate due to its thin layers. The coverage of **Marmorino Tintoretto™** is in regards to its 2 coat application.

One Quart (1.0 kg (2.2 lbs)) roughly 10 sq ft

One Gallon (5.0 kg (11lbs)) roughly 50 sq ft

One Bucket (20 kg (44lbs)) roughly 200 sq ft

### APPLICATION STEPS

1. Prepare Substrate
2. Prime Substrate
3. First Coat Application
4. Finish Coat Application
5. Seal Plaster With Meoded **Hydrowax™** or Meoded Sealer

### PREPARATION

Masking - Tape, mask and cover adjacent surfaces to protect them from splatter.

### PRIMING

- **New Drywall Surface** - Prime substrates with PVA acrylic primer and let it dry fully. Apply one coat of **Meoded Quartz Primer™**, allowing it at least 3-5 hours to dry.
- **Existing Surface** - Any surface with sheen should be sanded lightly, cleaned and dust free. Then prime the surface with multi-purpose primer and let it dry fully. Next, apply one coat of **Meoded Quartz Primer™**, allowing it to dry for at least 3-5 hours. Preparation of flat surfaces requires only the application of **Meoded Quartz Primer™**.
- **Exterior Brown Coat** - Surface should be pressure washed and clean. When surface is fully dry, apply **Meoded Quartz Primer™** diluted up to 25% water. Let it dry for at least 3-5 hours. Over the brown coat, it is recommended to apply three thin coats of **Marmorino Tintoretto™** to get a smooth surface.

### MIXING

**Marmorino Tintoretto™** is shipped as a white paste. If tinted, mix **Marmorino Tintoretto™** to distribute colorants evenly. If needed, dilute with a small amount of clean portable water for easier mixing. Use clean tools for mixing. Avoid contaminating plaster materials with any foreign matter such as dirt, dust and debris.



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA 90038  
1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

## INSTALLATION

Use a stainless steel trowel or spatula. Meoded offers a wide variety of specialty plaster tools including stainless steel trowels and spatulas used to install **Marmorino Tintoretto™**.

### FIRST COAT

Should be applied thinly and evenly, covering the entire wall. It is important to understand that with **Marmorino Tintoretto™**, any imperfections from the first coat will be seen in the second coat. To eliminate trowel marks, it is recommended to use a damp sponge in a circular motion or to continue to clean with the trowel before the **Marmorino Tintoretto™** dries. This will prevent you from seeing any natural movement marks on the second coat. In order to see the movement marks on the second coat, leave the first coat as is, spread thinly and evenly across the wall.

### SECOND COAT (Smooth Finish)

If required to smooth, lightly sand the first coat with 150-220 grit sandpaper before proceeding and clean the dust. Apply second coat in the same manner as first coat. When material is still moist, smooth surface repeatedly with clean trowel. After 5 minutes, burnish the surface by holding the trowel at about a 40 degrees angle and keep smoothing with pressure until required sheen and smoothness level is achieved. Avoid formation of dark trowel marks.

### SECOND COAT (Distressed Finish)

Apply material in patches leaving gaps to reveal first coat. Smooth surface repeatedly with clean trowel. When material has set sufficiently, trowel again until required smoothness is achieved. Avoid formation of dark trowel marks.

## CUSTOM FINISHES

A mock-up or an approved sample board should be used as a standard for a custom finish project. Meoded provides personal consultation services to help develop custom applications.

## SPECIAL EFFECTS

To enhance the elegant and rich appearance of **Marmorino Tintoretto™**, unique Metallic effects and custom stencils can be integrated.

## SEALER/WAX

After a minimum of 48 hours of dry time, it is recommended to protect the product with either a sealer or wax. It is recommended to use Meoded's penetrating sealer to provide the finish with protection from moisture and dirt, while not adding sheen or changing the color. If sheen is desired, it is recommended to apply **Meoded's Hydrowax™**, which will add a low sheen finish on top of the **Tintoretto™**. **Hydrowax™** is only for interior finishes while the sealer can be used both interior and exterior.

## CLEAN UP

Remove temporary protection, such as masking tape and covers. Clean up spills and splatters using methods that will not damage the surfaces.

## DELIVERY, STORAGE AND HANDLING

Keep materials away from direct sunlight. Store them in original, unopened packages in a dry, dark location at temperatures between 45 to 95 degrees F. Always wear OSHA-compliant eye protection. Wear a respirator to sand or scrape the product. Work only in well-ventilated areas. Avoid prolonged skin contact. Avoid working with the material in temperatures below 45 degrees F or above 95 degrees F. Keep away from children. Do not use products older than one year. Read the entire SDS and product labels.



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA 90038  
1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

## APPEARANCE TOLERANCES

The application and field conditions may alter the product's appearance. Colors and textures displayed on color cards and product samples are approximate, not exact. Contractors should prepare mock-ups and/or samples to display the actual materials and workmanship prior to final approval. Mottling and variations in appearance and hue are a normal part of any plaster surface and add to **Marmorino Tintoretto™**'s aesthetic appeal.

## AVAILABILITY

Meoded products are sold through the company's network of distributors throughout the United States. Contact Meoded or visit our website [www.meodedPaint.com](http://www.meodedPaint.com) for referrals to local sources.

## WARRANTY

**Meoded Paints & Decoration™** warrants its products for the purpose in which they were intended for, when applied and used in accordance with manufacturer's instructions within 10 months of production date. Warranty period of Meoded's products is 5 years from the date of installation. **Meoded Paints & Decoration™** reserves the right to inspect installations prior to resolving any claims made under this warranty. This limited warranty is exclusive and in lieu of all other warranties; either written, oral or otherwise implied. **Meoded Paints & Decoration™** also excluded any liability for consequential damages. Meoded's liability under this warranty is limited to the replacement of products found to be defective or refund to the original purchaser, with proof of purchase.

## CLEANING AND MAINTENANCE

### CLEANING

Use a dry cloth to remove dust and loose dirt from surfaces, then wipe them with a clean damp cloth as needed. Mild detergents or proprietary cleaning agents may also be used. Scrub gently or use a low-pressure water stream if necessary. Solvents such as acetone or mineral spirits can also be used, provided proper safety procedures are observed. Clean vertical surfaces moving upward from the bottom. Use a damp rag followed by a dry rag to remove any remaining cleaning agents. Find a small, inconspicuous portion of the surface to test cleaning products and methods before applying them to a wider area. Follow the manufacturer's package label instructions.

### BLEMISHES

Some scuff marks, scratches and stains that resist normal cleaning techniques may respond to light sanding with 1000-grit sandpaper or the finest grade steel wool. Find a small, inconspicuous portion of the surface to test these techniques. Reapply sealer and/or wax to sanded areas as necessary.

### WARNING!

This product may contain traces of chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.



## **TECHNICAL SERVICES & SUPPORT**

Meoded provides customers with any level of assistance that may need to gain full value from our products. Designers can call upon our professional staff to match colors or create new colors for custom installations. We're ready to provide color charts and sample boards for texture evaluations and comparisons. Installers can call upon our master craftsman for advice and guidance at every step of the installation process. If you have any questions whatsoever, our enthusiastic and courteous staff will provide the support you need to experience the **Marmorino Tintoretto™** advantage.

Every Meoded product comes with instructions that are more than adequate to guide any finish contractor or homeowner to a successful installation. In addition, we offer professional seminars for applicators of all skill and experience levels. We teach everything from the basic installation steps to tips and techniques for artists and artisans. You can also find a detailed YouTube video for application tips.

Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA 90038  
1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)