



Manufactured by Meoded Paints & Decoration
6314 Santa Monica Blvd., Los Angeles, CA 90038
1-323-308-2600 | www.meodedPaint.com

Stucco Lamundo™

Venetian Plaster - Gloss Finish

Zero VOC / Eco Friendly

Meoded Stucco Lamundo™ is a genuine lime-based Venetian Plaster formulated for easy application and exceptional durability. This interior wall coating system is a tintable paste which allows the achievement of highly polished marble-like finish on almost any interior surface. Formulated with limestone, Stucco Lamundo™'s thin layer application creates the illusion of depth and color variation. Lamundo is particularly elegant and is designed for precious wall spaces for both residential, commercial spaces, and any environment where a high-end atmosphere is desired.

COLORS

Stucco Lamundo™ can be tinted to any color using Universal tints or machine colorants. Meoded's natural concentrated "VOC free" pigments are recommended for dark colors.

SIZE AND COVERAGE

Stucco Lamundo™ yields a high coverage rate due to its thin layers. The coverage of Stucco Lamundo™ is in regards to its 3 layer application.

One Quart (1.0 kg (2.2 lbs)) roughly 20 sq ft

One Gallon (5.0 kg (11lbs)) roughly 100 sq ft

One Bucket (20 kg (44 lbs)) roughly 400 sq ft

APPLICATION STEPS

1. Prepare Substrate
2. Prime Substrate
3. First Coat Application
4. Second Coat Application
5. Third Coat /Burnishing Application
6. Seal Plaster With Meoded **Hydrowax™** or Meoded Sealer

PREPARATION

Masking - Tape, mask and cover adjacent surfaces to protect them from splatter.

PRIMING

- **New Surface** - Prime substrates with PVA acrylic primer and let it dry fully. Apply one coat of **Meoded Quartz Primer™**, allowing it at least 3-5 hours to dry.
- **Existing Surface** - Any surface with sheen should be sanded lightly, cleaned and dust free. Then prime the surface with multi-purpose primer and let it dry fully. Next, apply one coat of **Meoded Quartz Primer™**, allowing it to dry for at least 3-5 hours. Preparation of flat surfaces requires only the application of **Meoded Quartz Primer™**.

MIXING

Stucco Lamundo™ is shipped as a white paste. If tinted, mix **Stucco Lamundo™** to distribute colorants evenly. If needed, dilute with a small amount of clean portable water for easier mixing. Use clean tools for mixing. Avoid contaminating plaster materials with any foreign matter such as dirt, dust and debris.

INSTALLATION

Use a stainless steel trowel or spatula. Meoded offers a wide variety of specialty plaster tools including stainless steel trowels and spatulas used to install **Stucco Lamundo™**.

FIRST COAT

The first coat of **Stucco Lamundo™** should be applied in a thin and even manner, covering the entire wall. Allow at least 12 hours for the first coat to dry.



Manufactured by Meoded Paints & Decoration
6314 Santa Monica Blvd., Los Angeles, CA 90038
1-323-308-2600 | www.meodedPaint.com

SECOND COAT

If required to smooth, lightly sand the first coat with 180-320 grit sandpaper before proceeding. The second coat should be applied and spread tightly in overlapping patch patterns. Allow the second coat to dry for at least 5-7 hours.

THIRD COAT & BURNISHING

Apply the finish coat in the same manner as the second coat. Yet, when the material is still moist, start pressing, smoothing and gradually burnish the material in 10-15 sq. ft. sections. The more you burnish the shinier and smoother the surface will become.

CUSTOM FINISHES

A mock-up or an approved sample board should be used as a standard for a custom finish project. Meoded provides personal consultation services to help develop custom applications.

SPECIAL EFFECTS

To enhance the elegant and rich appearance of **Stucco Lamundo™**, unique Metallic effects and custom stencils can be integrated.

WAX

After a minimum of 48 hours of dry time, it is recommended to apply a layer of Meoded **Hydrowax™** to protect your finish from moisture and dirt. **Hydrowax™** also enhances sheen and gloss. Use a clean spatula or trowel to apply a thin layer of wax. Work the wax on the surface and remove any excess. Buffing the surface produces a polished effect.

SEALER

If no extra shine is desired on the finish, apply two to three coats of an Meoded's penetrating sealer to protect the product from moisture and dirt.

CLEAN UP

Remove temporary protection, such as masking tape and covers. Clean up spills and splatters using methods that will not damage the surfaces.

DELIVERY, STORAGE AND HANDLING

Keep materials away from direct sunlight. Store them in original, unopened packages in a dry, dark location at temperatures between 45 to 95 degrees F. Always wear OSHA-compliant eye protection. Wear a respirator to sand or scrape the product. Work only in well-ventilated areas. Avoid prolonged skin contact. Avoid working with the material in temperatures below 45 degrees F or above 95 degrees F. Keep away from children. Do not use products older than one year. Read the entire SDS and product labels.

APPEARANCE TOLERANCES

The application and field conditions may alter the product's appearance. Colors and textures displayed on color cards and product samples are approximate, not exact. Contractors should prepare mock-ups and/or samples to display the actual materials and workmanship prior to final approval. Mottling and variations in appearance and hue are a normal part of any plaster surface and add to **Stucco Lamundo™**'s aesthetic appeal.

AVAILABILITY

Meoded products are sold through the company's network of distributors throughout the United States. Contact Meoded or visit our website www.meodedPaint.com for referrals to local sources.



Manufactured by Meoded Paints & Decoration
6314 Santa Monica Blvd., Los Angeles, CA 90038
1-323-308-2600 | www.meodedPaint.com

WARRANTY

Meoded Paints & Decoration™ warrants its products for the purpose in which they were intended for, when applied and used in accordance with manufacturer's instructions within 10 months of production date. Warranty period of Meoded's products is 5 years from the date of installation. **Meoded Paints & Decoration™** reserves the right to inspect installations prior to resolving any claims made under this warranty. This limited warranty is exclusive and in lieu of all other warranties; either written, oral or otherwise implied. **Meoded Paints & Decoration™** also excludes any liability for consequential damages. Meoded's liability under this warranty is limited to the replacement of products found to be defective or refund to the original purchaser, with proof of purchase.

CLEANING

Use a dry cloth to remove dust and loose dirt from surfaces, then wipe them with a clean damp cloth as needed. Mild detergents or proprietary cleaning agents may also be used. Scrub gently or use a low-pressure water stream if necessary. Solvents such as acetone or mineral spirits can also be used, provided proper safety procedures are observed. Clean vertical surfaces moving upward from the bottom. Use a damp rag followed by a dry rag to remove any remaining cleaning agents. Find a small, inconspicuous portion of the surface to test cleaning products and methods before applying them to a wider area. Follow the manufacturer's package label instructions.

BLEMISHES

Some scuff marks, scratches and stains that resist normal cleaning techniques may respond to light sanding with 1000 grit sandpaper or the finest grade steel wool. Find a small, inconspicuous portion of the surface to test these techniques. Reapply sealer or wax to sanded areas as necessary.

REPAIRS

The application style of **Stucco Lamundo™** makes it easy to blend-in repairs. Contact Meoded for details.

WARNING!

This product may contain traces of chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

TECHNICAL SERVICES & SUPPORT

Meoded provides customers with any level of assistance that may need to gain full value from our products. Designers can call upon our professional staff to match colors or create new colors for custom installations. We're ready to provide color charts and sample boards for texture evaluations and comparisons. Installers can call upon our master craftsman for advice and guidance at every step of the installation process. If you have any questions whatsoever, our enthusiastic and courteous staff will provide the support you need to experience the **Stucco Lamundo™** advantage.

Every Meoded product comes with instructions that are more than adequate to guide any finish contractor or homeowner to a successful installation. In addition, we offer professional seminars for applicators of all skill and experience levels. We teach everything from the basic installation steps to tips and techniques for artists and artisans. You can also find a detailed YouTube video for application tips.