



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA  
90038 1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

## **Marmorino Palladino™**

### *Lime Slurry Finish*

### *Zero VOC / Eco Friendly*

**Meoded Lime Slurry Finish** is a thick, brush-applied mineral coating that creates a beautifully aged, textured appearance on brick, stone, and masonry surfaces. To create the Lime Slurry, simply dilute Meoded Marmorino Palladino lime plaster with 5–10% clean water, transforming it into a rich slurry consistency that can be brushed directly onto clean absorbent masonry surfaces. Thicker and more textured than traditional limewash, Lime Slurry adds depth, movement, and old-world character while maintaining the breathability, durability, and natural beauty of authentic lime plaster. Suitable for both interior and exterior applications.

### **COLORS**

**Marmorino Palladino™ Lime Slurry** can be tinted to any of Meoded's 88 carefully curated colors or custom color matched to nearly any shade, offering limitless design possibilities while maintaining the authentic beauty of a natural lime finish.

### **SIZE AND COVERAGE**

**Lime Slurry** yields a high coverage rate due to its thin layers and dilution. The coverage of **Lime Slurry** is in regards to its 2 layer application.

One Quart (1.0 kg (2.2 lbs)) roughly 13-15 sq ft  
One Gallon (5.0 kg (11lbs)) roughly 65-75 sq ft  
One Bucket (20 kg (44lbs)) roughly 260-300 sq ft

### **APPLICATION STEPS**

1. Prepare Substrate
2. Prime Substrate if non absorbent
3. First Coat Application

4. Finish Coat Application
5. Seal Lime Slurry with Meoded Stain Shield Sealer

### **PREPARATION**

Masking - Tape, mask and cover adjacent surfaces to protect them from splatter.

### **PRIMING**

• **Unpainted and Unsealed Brick, Stone & Masonry (No Primer Needed)** – Surface should be clean, structurally sound, and free from dust, dirt, grease, oil, mildew, efflorescence, loose particles, or any contaminants that may affect adhesion. Lightly mist the surface with clean water prior to application. The substrate should be damp, but not saturated or dripping wet.

• **Previously Painted Brick, Masonry, Concrete & Stucco (Primer Required)** – Remove any loose or flaking paint and ensure the surface is clean, dry, and free of dust and contaminants. Previously painted surfaces with a flat finish can be primed directly with one coat of Meoded Quartz Primer™ and allowed to dry for at least 3–5 hours before applying the Lime Slurry. Surfaces with sheen or gloss should be lightly sanded, cleaned of all dust, primed with a quality multi-purpose primer, and then coated with one coat of Meoded Quartz Primer™. Allow the Quartz Primer™ to dry for at least 3–5 hours before application of the Lime Slurry finish.

• **Exterior Masonry Surfaces** – Brick, stone, stucco, and masonry surfaces should be thoroughly cleaned and free of dirt, dust, mildew, efflorescence, and loose material. Pressure washing is recommended when appropriate. Allow the surface to dry completely before application. Lightly mist the substrate with clean water prior to applying the first coat of Lime Slurry.

### **MIXING**

To create the Lime Slurry effect, dilute Marmorino Palladino™ with approximately 5–10% clean potable water and mix thoroughly until a smooth, brushable slurry consistency is



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA  
90038 1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

achieved. If tinted, thoroughly mix the material before application to ensure the colorants are evenly dispersed throughout the plaster. Additional small amounts of water may be added as needed to achieve the desired application consistency. Always use clean tools and equipment when mixing. Avoid contaminating the material with dirt, dust, debris, or other foreign matter, as this may affect the appearance and performance of the finished surface.

## INSTALLATION

Apply Lime Slurry using a Meoded Large Box Brush. The Lime Slurry should be brushed onto the surface in horizontal patterns, working from the bottom of the wall upward while maintaining a wet edge throughout the application. Be sure to work the material thoroughly into the brick joints, surface texture, and masonry profile for a natural, uniform appearance. Meoded offers specialty box masonry brushes specifically designed to create authentic Lime Slurry, Lime Wash, and mineral finish effects.

### FIRST COAT

Apply the first coat of Lime Slurry using a Meoded Large Box Brush, working from the bottom of the wall upward in horizontal brush strokes. Ensure the material is worked thoroughly into all brick joints, surface textures, and masonry voids while maintaining a wet edge throughout the application. The first coat should be applied evenly to establish uniform coverage while allowing the natural texture of the substrate to remain visible. Allow the first coat to dry for approximately 8–10 hours before applying the second coat.

**SECOND COAT** Apply the second coat of Lime Slurry in the same manner as the first coat using a Meoded Large Box Brush. Prior to application, lightly mist the surface with clean water approximately 20 minutes beforehand to

help promote proper workability and adhesion. Apply the second coat evenly, ensuring complete coverage while maintaining the natural movement and texture characteristic of a Lime Slurry finish. Work the material thoroughly into all brick joints, masonry textures, and surface irregularities. Depending on the desired look, the second coat may be applied slightly heavier to create additional depth and texture.

### SEALER

Allow the final coat of Marmorino Palladino™ Lime Slurry to cure for a minimum of 48 hours before sealing. Apply 2–3 coats of Meoded Stain Shield™ Natural Look Sealer, working from the bottom of the wall upward to help prevent runs and drips. Apply the sealer evenly using a brush, sponge, roller, or sprayer, ensuring complete coverage without over-applying the material. Avoid excessive application, as heavy coats may result in drips, uneven absorption, or surface inconsistencies. Allow each coat to dry thoroughly before applying subsequent coats. Stain Shield helps protect the Lime Slurry finish from moisture, dirt, and everyday wear while preserving its natural matte appearance, color variation, and mineral character. Sealing is highly recommended for exterior applications, fireplaces, high-traffic areas, and surfaces exposed to moisture or frequent cleaning.

### CLEAN UP

Remove temporary protection, such as masking tape and covers. Clean up spills and splatters using methods that will not damage the surfaces.



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA  
90038 1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

## **DELIVERY, STORAGE AND HANDLING**

Keep materials away from direct sunlight. Store them in original, unopened packages in a dry, dark location at temperatures between 45 to 95 degrees F. Always wear OSHA-compliant eye protection. Wear a respirator to sand or scrape the product. Work only in well-ventilated areas. Avoid prolonged skin contact. Avoid working with the material in temperatures below 45 degrees F or above 95 degrees F. Keep away from children. Do not use products older than one year. Read the entire SDS and product labels.

## **APPEARANCE TOLERANCES**

The application and field conditions may alter the product's appearance. Colors and textures displayed on color cards and product samples are approximate, not exact. Contractors should prepare mock-ups and/or samples to display the actual materials and workmanship prior to final approval. Mottling and variations in appearance and hue are a normal part of any plaster surface and add to **Marmorino Palladino™**'s aesthetic appeal.

## **AVAILABILITY**

Meoded products are sold through the company's network of distributors throughout the United States. Contact Meoded or visit our website [www.meodedPaint.com](http://www.meodedPaint.com) for referrals to local sources.

## **WARRANTY**

**Meoded Paints & Decoration™** warrants its products for the purpose in which they were intended for, when applied and used in accordance with manufacturer's instructions within 10 months of production date. Warranty period of Meoded's products is 5 years from the date of installation. **Meoded Paints &**

**Decoration™** reserves the right to inspect installations prior to resolving any claims made under this warranty. This limited warranty is exclusive and in lieu of all other warranties; either written, oral or otherwise implied. **Meoded Paints & Decoration™** also excludes any liability for consequential damages. Meoded's liability under this warranty is limited to the replacement of products found to be defective or refund to the original purchaser, with proof of purchase.

## **CLEANING AND MAINTENANCE**

### **CLEANING**

Use a dry cloth to remove dust and loose dirt from surfaces, then wipe them with a clean damp cloth as needed. Mild detergents or proprietary cleaning agents may also be used. Scrub gently or use a low-pressure water stream if necessary. Solvents such as acetone or mineral spirits can also be used, provided proper safety procedures are observed. Clean vertical surfaces moving upward from the bottom. Use a damp rag followed by a dry rag to remove any remaining cleaning agents. Find a small, inconspicuous portion of the surface to test cleaning products and methods before applying them to a wider area. Follow the manufacturer's package label instructions.

### **BLEMISHES**

Some scuff marks, scratches and stains that resist normal cleaning techniques may respond to light sanding with 1000-grit sandpaper or the finest grade steel wool. Find a small, inconspicuous portion of the surface to test these techniques. Reapply sealer to sanded areas as necessary.



Manufactured by Meoded Paints & Decoration  
6314 Santa Monica Blvd., Los Angeles, CA  
90038 1-323-308-2600 | [www.meodedPaint.com](http://www.meodedPaint.com)

## **WARNING!**

This product may contain traces of chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

## **TECHNICAL SERVICES & SUPPORT**

Meoded provides customers with any level of assistance that may need to gain full value from our products. Designers can call upon our professional staff to match colors or create new colors for custom installations. We're ready to provide color charts and sample boards for texture evaluations and comparisons. Installers can call upon our master craftsman for advice and guidance at every step of the installation process. If you have any questions whatsoever, our enthusiastic and courteous staff will provide the support you need to experience the

**Marmorino Palladino™** advantage.

Every Meoded product comes with instructions that are more than adequate to guide any finish contractor or homeowner to a successful installation. In addition, we offer professional seminars for applicators of all skill and experience levels. We teach everything from the basic installation steps to tips and techniques for artists and artisans. You can also find multiple detailed YouTube videos for application tips on textures and finishes achievable with Palladino.